

MATERIAL SAFETY DATA SHEET

SAFETEC OF AMERICA	May be used to comply with OSHA's Hazard Communication Standard 29 CFR 1910.1200. Standard must be consulted for specific requirements.				HMIS HAZARD RATING			
	HEALTH	1	0 = INSIGNIFICANT		3 = HIGH			
	FLAMMABILITY	1	1 = SLIGHT		4 = EXTREME			
	REACTIVITY	1	2 = MODERATE					
TRANSPORTATION INFORMATION								
PROPER SHIPPING NAME			Not Regulated					
HAZARD CLASS/PKG. GRP.			None/None		REF.	N/A		
IDENTIFICATION NUMBER			None		LABEL	None Required		

SECTION 1 - PRODUCT / COMPANY IDENTIFICATION

IDENTITY (AS USED ON LABEL AND LIST)		Page 1 of 2	
ACID LOCK™			
MANUFACTURER'S NAME		EMERGENCY TELEPHONE NUMBER (24 Hours)	
Safetec of America, Inc.		(800) 255-3924	
ADDRESS (NUMBER, STREET, P.O. BOX)		TELEPHONE NUMBER FOR INFORMATION	
887 Kensington Ave.		(716) 895-1822	
(CITY, STATE AND ZIP CODE)		DATE PREPARED	January 7, 2009
Buffalo, NY 14215		SUPERSEDES	September 21, 2007

SECTION 2 - HAZARDOUS INGREDIENTS / IDENTITY INFORMATION

HAZARDOUS COMPONENTS (SPECIFIC CHEMICAL IDENTITY; COMMON NAME(S))	CAS #	% (wt.) (OPTIONAL)	ACGIH TLV/TWA/STEL			
			PPM	MG/M ³	PPM	MG/M ³
Inorganic alkali salt, CAS proprietary		45-65	None Established			5 (TLV)
Superabsorbent polymer, CAS proprietary		45-65		5 (PEL)		5 (TLV)

This product is not known to contain a substance subject to Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA) and 40 CFR 372 at or above minimal amounts.

SECTION 3 - HEALTH HAZARD DATA

ROUTES OF ENTRY - SIGNS AND SYMPTOMS OF EXPOSURE	EMERGENCY AND FIRST AID PROCEDURES
INHALATION: Breathing of dust may cause throat and upper respiratory tract irritation.	Remove to fresh air; seek medical attention if required.
EYES: May cause moderate irritation associated with redness and burning sensation.	Flush eyes with clear running water for a minimum of 15 minutes while holding eyelids open; if irritation persists, seek medical attention.
INGESTION: Ingested in quantity, material may cause burning of mouth, throat and esophagus, and stomach.	Drink large amounts of water. DO NOT induce vomiting. Seek medical attention.
SKIN: Prolonged contact with skin may cause moderate irritation.	Wash thoroughly with soap and water; if irritation persists, seek medical attention.

HEALTH HAZARDS (ACUTE AND CHRONIC): Acute effects are irritation of the eyes, including corneal opacities; dusts and mists are irritating to the skin, mucous membranes and upper respiratory tract. Chronic effects are inflammation of the mucous membranes in the respiratory tract and of the skin.

CARCINOGENICITY	NTP?	No	IARC MONOGRAPHS?	No	OSHA REGULATED?	No
No additional information						

MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE:
Pre-existing skin or breathing disorders may become aggravated through exposure.

MATERIAL SAFETY DATA SHEET

IDENTITY (AS USED ON LABEL AND LIST)

ACID LOCK™

Page 2 of 2

Date: January 7, 2009

SECTION 4 - FIRE FIGHTING MEASURES

FLASH POINT (METHOD USED)

Not Applicable

FLAMMABLE LIMITS (% Volume in Air for Lowest Flashing Component)

LEL: N/A

UEL: N/A

EXTINGUISHING MEDIA

Water, dry chemicals, foam, CO₂

SPECIAL FIRE FIGHTING PROCEDURES

Use water spray to cool fire-exposed containers and structures.

UNUSUAL FIRE AND EXPLOSIVE HAZARDS

Spilled material swells and becomes extremely slippery when wet. Use standard safety precautions for finely divided powders. Thermal decomposition may emit toxic and irritating substances.

SECTION 5 - PRECAUTIONS FOR SAFE HANDLING AND USE/LEAK PROCEDURES

STEPS TO BE TAKEN IF MATERIAL IS SPILLED OR RELEASED

In case of accidental spills, provide adequate ventilation; avoid generating dust. Vacuum (using HEPA filter equipped system) if possible to avoid generating airborne dust. Place spilled material into a clean, dry container for disposal.

WASTE DISPOSAL METHODS

Dispose of in accordance with Local, State, and Federal regulations. Products classified as non-hazardous may become hazardous waste upon contact with other products. Refer to "40 CFR Protection of Environment Parts 260-299" for complete waste disposal regulations. Consult your Local, State, or Federal Environmental Protection Agency before disposing of any chemicals.

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE

Keep container(s) tightly closed when not in use. Store in cool, dry area. Keep this and other chemicals out of reach of children.

SECTION 6 - EXPOSURE CONTROLS/PERSONAL PROTECTION

RESPIRATORY PROTECTION

Use NIOSH/MSHA approved or equivalent with high efficiency filter for particulate levels above 0.05mg/m³

VENTILATION

LOCAL EXHAUST: Recommended
MECHANICAL (GENERAL): As appropriate

PROTECTIVE GLOVES

Impervious/chemical resistant

EYE PROTECTION

Safety goggles

OTHER PROTECTIVE CLOTHING OR EQUIPMENT

Ordinarily, none required.

WORK/HYGIENIC PRACTICES

Practice safe work habits. Use according to label instructions.

SECTION 7 - PHYSICAL/CHEMICAL PROPERTIES

BOILING POINT

Not Applicable

SPECIFIC GRAVITY (WATER = 1)

50.3 lb./cu.ft.

VAPOR PRESSURE (mm Hg)

Not Applicable

MELTING POINT

>1569°F (partial to full decomposition)

VAPOR DENSITY (AIR = 1)

Not Applicable

pH (1% solution)

11.5

SOLUBILITY IN WATER

Slight

EVAPORATION RATE (n-BUTYL ACETATE=1)

Not applicable

APPEARANCE AND ODOR

Off-white, granular powder; odorless

% VOLATILES (BY WEIGHT)

Not applicable

SECTION 8 - STABILITY AND REACTIVITY

STABILITY

UNSTABLE:

STABLE: XXX

CONDITIONS TO AVOID

High humidity, extreme temperatures

INCOMPATIBILITIES (MATERIALS TO AVOID)

Contact with sugars may produce high levels of carbon monoxide in enclosed areas.

HAZARDOUS DECOMPOSITION OR BYPRODUCTS

Decomposition will not occur if handled/stored properly. Thermal decomposition may emit toxic and irritating substances.

HAZARDOUS POLYMERIZATION MAY OCCUR:

WILL NOT OCCUR: XXX

CONDITIONS TO AVOID

None known

The information contained herein is believed to be accurate but is not warranted to be so. Users are advised to confirm in advance of need that information is current, applicable and suited to the circumstances of use. Vendor assumes no responsibility for injury to vendee or third persons proximately caused by the material if reasonable safety procedures are not adhered to as stipulated in the data sheet. Furthermore, vendor assumes no responsibility for injury caused by abnormal use of this material even if reasonable safety procedures are followed.